

## ALSAN FLASHING

**Description:** **ALSAN FLASHING** is a waterproofing one-component polyurethane / bitumen resin. It is dedicated to roof flashings and details where it is difficult to apply waterproofing membranes.

**ALSAN FLASHING** is ready to use. It is applied directly on traditional bituminous waterproofing membrane, without any primer and on other media such as wood, metal and concrete.

**Installation:** **ALSAN FLASHING** is applied with a brush or roller in 2 or 3 layers on a clean and sound substrate. Mix well the product before usage.

Transitions, changes in plan and junctions between two supports, must be reinforced with **FLASHING REINFORCEMENT**, applied right after the first layer of **ALSAN FLASHING**.

**ALSAN FLASHING** is UV resistant. It can be left exposed without protection. The top coat can also be covered with roofing granules for aesthetic purposes.

Minimum application temperature: 5 °C (41 °F)

**Packaging and consumption:**

- 3.78 L and 19 L pails
- Average consumption: 0.75 L/m<sup>2</sup> per coat
- Storage: Up to 9 months in original sealed containers
- Keep away from any source of heat and dampness

**Properties:**

Properties	ALSAN FLASHING
Physical state	Brown viscous liquid
Density at 25 °C (g/L)	1070
Solids content (%)	80
Flash point (°C)	2.5
Softening point (°C)	150 (302 °F)
Flammability	Flammable
Drying time	Ready to recoat after 2 hours Dry: 12 hours (remains tacky to touch)

(All values are nominal)

**Special indications:**

**Safety instructions**

- Flammable before curing
- Contains isocyanates. Consult Material Safety Data Sheet
- Harmful by inhalation
- Avoid skin contact
- Keep away from sources of ignition – No smoking