



Physical Properties

Appearance Black liquid	Consistency @ 77° F Light-bodied liquid	Solids By Volume 38.8%
Base Air blown asphalt	Flash Point -138° F (ASTM D-3278)	Solids By Weight 44.8%
CARB:Primer Max. MIR 1.20	Maximum VOC 550 g/l	Weight Per Gallon 7.34 lbs
Color Black	Maximum VOS 4.59lbs/gal	

Approvals and Certifications

Meets or exceeds the requirements of ASTM D-41, and Federal Specification SS-A-701B.

Description

HE104Q - QUICKDRY ASPHALT PRIMER (AEROS OL CAN) is a light-bodied, asphalt based material designed for priming surfaces prior to the application of hot-mopped or cold-applied asphalt coatings, roof cements and asphalt-based roof and flooring adhesives. Its highly penetrating qualities help assure a firm, tough bond.

NOTE: **HE104Q - QUICKDRY ASPHALT PRIMER (AEROS OL CAN)** in the spray can size complies with Air Quality Management District regulations.

Usage

- Metal edging and flashings
- Weathered composition roofing
- Concrete and masonry surfaces (prior to the use of solvent-based asphalt coatings or adhesives)
- Gypsum surfaces (prior to the use of solvent-based asphalt coatings or adhesives)
- Roofing surfaces prior to application of **Ruftac®** or other SBS self-adhering membrane

NOTE: For priming concrete, masonry or other porous surfaces to receive asphalt emulsion, use the emulsion diluted 20% with water.

Coverage

Coverage is 33 sq. ft. per can depending on porosity of surface.

Surface Preparation

Surface must be clean, dry, free of moisture as well as grease and oil.

Application

Shake can vigorously until ball rattles freely before using. Apply with good coverage to a clean, dry surface. Allow to dry thoroughly before applying coatings or adhesives. Avoid over-application and build-up of surface film. After spraying, turn can upside down, point nozzle into refuse can or at paper and push spray head for about 2 seconds to clear valve. If valve clogs, remove from can and clean in paint thinner.

Cleanup

Equipment can be cleaned with kerosene or mineral spirits. Clean hands with waterless hand cleaner. Use care in handling solvents.

Caution

DANGER! EXTREMELY FLAMMABLE! DO NOT PUNCTURE, INCINERATE OR BURN CAN EVEN WHEN EMPTY. Exposure to heat or prolonged exposure to sun may cause bursting.

CAUTION! COMBUSTIBLE! Contains petroleum distillate and hydrocarbon propellants. Keep away from heat, sparks and flame. Do not heat container or store at temperatures greater than 110°F. CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **DANGER! HARMFUL OR FATAL IF SWALLOWED!** If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **USE ONLY WITH ADEQUATE VENTILATION!** Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains detectable amount of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

EMPLOYERS should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

17 OZ AEROSOL (1.65 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**