

MATERIAL INFORMATION SHEET

MIS # 1805 - ASPHALT SATURATED ROOFING FELTS

IMPORTANT:Read this Material Information Sheet before handling or disposing of this product. This product safety information is provided to help our customers with health, safety and/or environmental matters. We have taken reasonable effort to ensure that the test methods and sources for this data are correct and reliable, however, we give no warranty, expressed or implied, regarding its correctness. Since conditions or methods of handling and using this product are beyond our control, we do not assume responsibility and expressly disclaim liability for damages resulting from or connected with the handling, storage, use or disposal of the product.

NOTE: Under government regulations, a MSDS is not required for this product; it is an end use product.

SECTION 1 PRODUCT AND MANUFACTURER'S INFORMATION

Manufacturer/Supplier's Name: IKO Production Inc.
Address: 120 Hay Road
Wilmington, DE 19809
Emergency Phone: (905) 457-2880 - EXT. 3354
Product Name: Asphalt Saturated Roofing Felts
Chemical Name: Not applicable
Trade Name: Asphalt Felts, Type 30 Felt, No. 15 Felt, Shake Felt, BUR Felt, Plain Felt, Saturated Felt, Heavy Duty Felt, Kolamax, Shingle Underlay, Perforated Felt, ArmourGard Vapour Retardant.
Chemical Family: Not applicable
Formula: Asphalt on a cellulose fibre sheet.

SECTION 2 PREPARATION INFORMATION

Prepared/Reviewed By: HSE Department
Phone Number: (905) 457-2880 - EXT. 3354
Date: August 20, 2012

SECTION 3 HAZARDOUS INGREDIENTS

This material contains no hazardous materials. Asphalt on/in a cellulose fiber sheet.

SECTION 4 PHYSICAL DATA

Boiling Point: Not applicable
Specific Gravity: Not applicable
Vapor Pressure: Not applicable
Evaporation Rate: Not applicable
Appearance: Black felt
Odor: Slight petroleum odor

SECTION 5 FIRE AND EXPLOSION DATA

Flash Point: Not applicable
Flammable Limits: Not applicable
Extinguishing Media: Dry chemical, carbon dioxide, water
Special Procedures: Respirators required for fire fighting

MATERIAL INFORMATION SHEET

MIS # 1805 - ASPHALT SATURATED ROOFING FELTS

SECTION 6 TOXICOLOGICAL PROPERTIES

Exposure Limits: Not applicable
*Primary Route
of Exposure:* Not applicable
Exposure Effects: Not applicable

WARNING: This product may contain oxidized bitumens. The International Agency for Research on Cancer (the "IARC") issued a statement that "occupational exposure to oxidized bitumens and their emissions during roofing operations are probably carcinogenic to humans." This warning may be updated at such time as a final determination is made and IARC has published its monograph on the matter.

SECTION 7 REACTIVITY DATA

Stability: Stable
Polymerization: Will not occur
Materials to Avoid: Not applicable
*Hazardous
Decomposition
Products:* Not applicable

SECTION 8 PREVENTIVE MEASURES

Spill Procedure: Not applicable
Disposal Procedure: Standard waste disposal
Ventilation: Not applicable
Respiratory: Not applicable
Gloves: Not applicable
Eye Protection: Not applicable
Other: Not applicable

SECTION 9 FIRST AID PROCEDURES

Not applicable.