

■ Calgary ■ Edmonton ■ London ■ Moncton ■ Montreal ■ Ottawa ■ Quebec ■ Saskatoon ■ Toronto ■ Vancouver ■ Winnipeg

MAMMOUTH ELASTOCOL STICK

Description: *ELASTOCOL STICK* is a primer designed to enhance the adhesion of self-adhesive membranes on porous surfaces such as “**DENS GLASS GOLD**” and “**DENS DECK**” at temperatures above -10°C . It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal, and wood.

Application: *ELASTOCOL STICK* can be applied with a brush, a roll or a spray can. It must be thoroughly dry before applying the waterproofing membrane. *ELASTOCOL STICK* must be shaken well before use.

WARNING: Do not accelerate drying of *ELASTOCOL STICK* by heating it with a torch.

Average coverage, porous surfaces: 0.3 to 0.5 L/m²,
non-porous surfaces: 0.1 to 0.25 L/m².

Properties:

Properties	ELASTOCOL STICK
Specific gravity at 20°C (kg/l)	0.79
Colour	Red
Solids by Weight (%)	24
Viscosity, Brookfield (cP, 25°C)	200
Flash point (ASTM D93)	-30°C (0°F)
Drying time	15 to 60 minutes

(All values are nominal)

Packaging: 3.78 L, 19 L pails and 350 g spray cans.

Shelf life: Up to 2 years in original sealed containers, in cool and ventilated area.

Cleaning: Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

Precautions: *ELASTOCOL STICK* is a highly flammable product.

Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with the skin. In closed area, ventilate carefully using mechanical means if necessary. Do not pour residues in drains.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.