SPRAY ACCESSORIES & OPTIONS

Quick Change Displacement Pumps (All pump packages include connecting hardware).

 QC5030.
 4900 psi, 2.8 gpm

 QC4030.
 4000 psi, 3.0 gpm

 QC3640.
 3600 psi, 3.8 gpm

 QC2560.
 2400 psi, 6.0 gpm

 QC2075.
 1800 psi, 7.5 gpm

 QC1015.
 1000 psi, 15.0 gpm



Questions about which pump lower is right for a specific material or job application? Call Hennes-Johnson Equipment toll free at (800) 249-1349 for knowledgeable assistance.



Replacement Tips & Control Valves

- A. HJ174A Trigger Assembly Control Valve
- B. HJ174R Recirculating Assembly Control Valve
- C. HJ196 Spraying Systems Tip & Housing (.067 .099)
- D. **HJ175** Graco Tip & Housing (.021 .071)
- E. HJ198 Spraying Systems Orifice (.067 .099)
- F. **XHD XXX** Graco Tip Only (.021 .071)
- G. 206-236-XXX Dual Spray Nozzle
- H. HJ174B Pole Gun Ball Valve
- I. **HJ189** 3/8 in. Pressure Relief Valve (Bleed Valve)
- J. HJ180 1/2 in. Gun swivel

